



(12)

EUROPEAN PATENT APPLICATION

(21) Application number: 89250092.7

(51) Int. Cl. 5: E21B 23/00, E21B 23/04,
E21B 29/02, E21B 17/10

(22) Date of filing: 20.11.89

(30) Priority: 23.11.88 US 275265

1916 Christopher Drive
Everman Texas 76140(US)(43) Date of publication of application:
30.05.90 Bulletin 90/22(72) Inventor: Terrell, Jamie B.
1916 Christopher Drive
Everman Texas 76140(US)(64) Designated Contracting States:
BE DE FR GB NL(74) Representative: UEXKÜLL & STOLBERG
Patentanwälte
Beselerstrasse 4
W-2000 Hamburg 52(DE)

(71) Applicant: Terrell, Jamie B.

(54) Downhole chemical cutting tool.

(57) A downhole chemical cutting tool having an anchoring system employing interchangeable slip arrays (38) of progressively larger outside diameters that can be used economically to adjust the range of the anchoring system. The range can be further adjusted by utilizing interchangeable slip expansion mandrels (44). This anchoring system both anchors and centralizes the chemical cutting tool. The cutting tool includes a slip shaft (32) that provides fluid communication between the propellant section (24) and chemical section (26), thence to the slip piston (36) that receives the interchangeable slip arrays (38). The slip shaft and slip piston are threadedly connected to a set coiled tension spring (34). Interchangeable slip expansion mandrels (44) connected to the slip shaft (32) below the slip arrays are constructed with ball bearings (44a) on the surface that receives the slip arrays expanding the slip segments into a gripping engagement an usually large angle as the slip piston is actuated by the application of fluid pressure during the cutting operation. The interchangeable slips are configured so that the gripping teeth (38k,j,i,h) will simultaneously engage the internal surface (110) of the wellbore pipe being cut. During the cutting operation the application of fluid pressure activates the slip assembly and discharges the chemical cutting fluid from the chemical section into the fluid jet section of the tool at high tempera-

ture and velocity. After the release of fluid pressure the slip assembly reliably releases the tool due to the large angle of engagement of the slip segments.




FIG. 4



European
Patent Office

EUROPEAN SEARCH
REPORT

Application Number

EP 89 25 0092

DOCUMENTS CONSIDERED TO BE RELEVANT		Relevant to claim 1,5,8,18	CLASSIFICATION OF THE APPLICATION (Int. CL5) E 21 B 23/00 E 21 B 23/04 E 21 B 29/02 E 21 B 17/10
Category	Citation of document with indication, where appropriate, of relevant passages		
A,D	US-A-4 620 591 (TERRELL) * Abstract; figure 10 -----		
A,D	US-A-4 415 029 (PRATT) * Abstract; fig. * -----		
A,D	US-A-4 619 318 (TERRELL) * Abstract; fig. * -----		
A,D	US-A-4 345 646 (TERRELL) * Abstract; fig. * -----		
A,D	US-A-4 125 161 (CHAMMAS) * Abstract; fig. * -----		
A	DE-A-1 911 900 (LONGYEAR DIAMOND CORE DRILL SUPPLIERS) * Fig. * -----		
A	US-A-4 637 471 (SODERBERG) * Abstract; fig. * -----		
The present search report has been drawn up for all claims		TECHNICAL FIELDS SEARCHED (Int. CL5)	E 21 B
Place of search	Date of completion of search		
The Hague	17 May 91	WEIAND T.	
CATEGORY OF CITED DOCUMENTS			
X: particularly relevant if taken alone			
Y: particularly relevant if combined with another document of the same category			
A: technological background			
O: non-written disclosure			
P: intermediate document			
T: theory or principle underlying the invention			
E: earlier patent document, but published on, or after the filing date			
D: document cited in the application			
L: document cited for other reasons			
&: member of the same patent family, corresponding document			